



P-600/700
GLYCOL CIRCULATING PUMPS
UNION MODEL SX-3 SIMPLEX
1 1/2" NPT SUCTION x 3/4" NPT DISCHARGE
DESIGN: 2120 PSIG @ 130°F MAWP
(14617 kPag @ 54°C)
RATING: 1.84 USGPM
3 HP, 480/3/60 X-PROOF

F-400
GLYCOL PARTICULATE FILTER
CUNO MODEL 182
DESIGN: 175 PSIG @ 200°F MAWP
(1207 kPag @ 92°C MAWP)
RATING: 6 USGPM

F-401
GLYCOL CHARCOAL FILTER
CUNO MODEL 182
DESIGN: 175 PSIG @ 200°F MAWP
(1207 kPag @ 92°C MAWP)
RATING: 6 USGPM

E-400
AIR/GLYCOL HEAT EXCHANGER
6 - 5'-0" PASSES TRANE SERIES 32 FINNED TUBE
(20% EXCESS AREA)

H-400/T-400
GLYCOL REBOILER
PRESSON MODEL GR-250
DUTY: 250,000 BTU/HR

V-410
FUEL GAS SCRUBBER
8 5/8" OD x 3'-0" S/S
250 PSIG @ 200°F
(1724 kPag @ 92°C)

NOTES

- 1) PSV DISCHARGE TO BE O/S BUILDING AND LOW.
- 2) FUTURE FLASH TANK CONNECTION.

NO.	REVISION	BY	CHKD.	DATE
9	AS BUILT	KMS		04/11/29
8	REMOVED LSHH-410, REVISED AD-410 SYM	AB		04/11/18
7	REVISED AS SHOWN	AB		04/10/27
6	REVISED AS SHOWN	RWM		04/10/19
5	REVISED AS SHOWN	LM		04/09/14
4	REVISED TAG NUMBERS	LM		04/09/09
3	REVISED AS SHOWN	TBB		04/09/03
2	REVISED AS SHOWN	D.S.		04/08/25
1	GENERAL REVISIONS	KMS		04/08/23
0	ISSUED FOR CONSTRUCTION	CM		04/07/27

CUSTOMER REFERENCE: AB0200-003

Presson
ENERFLEX

CUSTOMER:					JOB NO.
PROJECT: GLYCOL DEHYDRATION UNIT P & ID					
TITLE:					
DRAWN	CHECKED	APPROVED	SCALE	DATE	DRAWING NUMBER
CM			NTS	04/07/16	