



NOTES

1) UNINSULATED OUTSIDE OF BUILDING
2) PROVIDED AND INSTALLED BY CUSTOMER

V-400
GLYCOL CONTACTOR
SIZE: 24" O.D. x 33'-0" S/S
(610 mm O.D. x 10058 mm S/S)
DESIGN: 2120 PSIG @ 130 / -20°F MDMT
(14617 kPag @ 54 / -29°C MDMT)

E-410
GAS/GLYCOL HEAT EXCHANGER
SIZE: 4 1/2" O.D. x 8 5/8" O.D. x 10'-0" LONG
(114.3 mm O.D. x 219 mm O.D. x 3048 mm LONG)
DESIGN: 2120 PSIG @ 130 / -20°F MDMT
(14617 kPag @ 54 / -29°C MDMT)

V-500
GLYCOL ACCUMULATOR BOTTLE
SIZE: 8 5/8" O.D. x 2'-0" S/S
(219mm O.D. x 610mm S/S)
DESIGN: 2120 PSIG @ 130 / -20°F MDMT
(14617 kPag @ 54 / -29°C MDMT)

BH-400 A/B
BUILDING HEATER
CATADYNE MODEL Wx24 x36
RATING: 24,000 BTU/HR
12 VDC c/w 30' START UP LEADS

BF-400
BUILDING EXHAUST FAN
6 ACPH
1/4 HP, 120/1/60 X-PROOF

NO.	REVISION	BY	CHKD.	DATE
5	AS BUILT	KMS		04/11/29
4	REVISED AS SHOWN	AB		04/10/28
3	REVISED AS SHOWN	LM		04/09/09
2	REVISED AS SHOWN	D.S.		04/08/25
1	GENERAL REVISIONS	KMS		04/08/23
0	ISSUED FOR CONSTRUCTION	CM		04/07/27
A	ISSUED FOR APPROVAL	CM		04/07/21

CUSTOMER REFERENCE
Presson ENERFLEX

CUSTOMER:					JOB NO.	
PROJECT:						
TITLE:						
GLYCOL DEHYDRATION UNIT						
DRAWN	CHECKED	APPROVED	SCALE	DATE	DRAWING NUMBER	SHT. 1 OF 2
CM			NTS	04/07/16		5